



# 1-Mbps QUAD DIGITAL ISOLATORS

Check for Samples: [ISO7240A](#), [ISO7241A](#), [ISO7242A](#)

## FEATURES

- 4000- $V_{peak}$  Isolation, 560- $V_{peak}$   $V_{IORM}$ 
  - UL 1577 , IEC 60747-5-2 (VDE 0884, Rev 2), IEC 61010-1, IEC 60950-1 and CSA Approved
- 4 kV ESD Protection
- Operate With 3.3-V or 5-V Supplies
- Typical 25-Year Life at Rated Working Voltage (See Application Note ([SLLA197](#)) and [Figure 10](#))
- High Electromagnetic Immunity (See Application Report ([SLLA181](#)))
- –40°C to 125°C Operating Range

## APPLICATIONS

- Industrial Fieldbus
- Computer Peripheral Interface
- Servo Control Interface
- Data Acquisition

## DESCRIPTION

See the [Product Notification](#) section. The ISO7240A, ISO7241A and ISO7242A are quad-channel digital isolators with multiple channel configurations and output enable functions. These devices have logic input and output buffers separated by TI's silicon dioxide (SiO<sub>2</sub>) isolation barrier. Used in conjunction with isolated power supplies, these devices block high voltage, isolate grounds, and prevent noise currents from entering the local ground and interfering with or damaging sensitive circuitry.


The ISO7240A has all four channels in the same direction while the ISO7241A has three channels the same direction and one channel in opposition. The ISO7242A has two channels in each direction.

The devices have TTL input thresholds and a noise-filter at the input that prevents transient pulses from being passed to the output of the device.

A periodic update pulse is sent across the barrier to ensure the proper dc level of the output. If this dc-refresh pulse is not received, the input is assumed to be unpowered or not being actively driven, and the failsafe circuit drives the output to a logic high state. (See ISO7240CF ([SLLS869](#)) or contact TI for a logic low failsafe option).

These devices may be powered from either 3.3-V or 5-V supplies on either side in any 3.3-V / 3.3-V, 5-V / 5-V, 5-V / 3.3-V, or 3.3-V / 5-V combination. Note that the signal input pins are 5-V tolerant regardless of the voltage supply level being used.

These devices are characterized for operation over the ambient temperature range of –40°C to 125°C.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

## FUNCTION DIAGRAM




Table 1. Device Function Table ISO724x <sup>(1)</sup>

| INPUT V <sub>CC</sub> | OUTPUT V <sub>CC</sub> | INPUT (IN) | OUTPUT ENABLE (EN) | OUTPUT (OUT) |
|-----------------------|------------------------|------------|--------------------|--------------|
| PU                    | PU                     | H          | H or Open          | H            |
|                       |                        | L          | H or Open          | L            |
|                       |                        | X          | L                  | Z            |
|                       |                        | Open       | H or Open          | H            |
| PD                    | PU                     | X          | H or Open          | H            |
| PD                    | PU                     | X          | L                  | Z            |

(1) PU = Powered Up; PD = Powered Down ; X = Irrelevant; H = High Level; L = Low Level

## AVAILABLE OPTIONS

| PRODUCT    | SIGNALING RATE | INPUT THRESHOLD                   | CHANNEL CONFIGURATION | MARKED AS | ORDERING NUMBER <sup>(1)</sup> |
|------------|----------------|-----------------------------------|-----------------------|-----------|--------------------------------|
| ISO7240ADW | 1 Mbps         | ~1.5 V (TTL)<br>(CMOS compatible) | 4/0                   | ISO7240A  | ISO7240ADW (rail)              |
|            |                |                                   |                       |           | ISO7240ADWR (reel)             |
| ISO7241ADW | 1 Mbps         | ~1.5 V (TTL)<br>(CMOS compatible) | 3/1                   | ISO7241A  | ISO7241ADW (rail)              |
|            |                |                                   |                       |           | ISO7241ADWR (reel)             |
| ISO7242ADW | 1 Mbps         | ~1.5 V (TTL)<br>(CMOS compatible) | 2/2                   | ISO7242A  | ISO7242ADW (rail)              |
|            |                |                                   |                       |           | ISO7242ADWR (reel)             |

(1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

|                 |   |                                    |  | VALUE     | UNIT |    |
|-----------------|---|------------------------------------|--|-----------|------|----|
| V <sub>CC</sub> | Supply voltage <sup>(2)</sup> , V <sub>CC1</sub> , V <sub>CC2</sub> |                                    |  | −0.5 to 6 | V    |    |
| V <sub>I</sub>  | Voltage at IN, OUT, EN  |                                    |  | −0.5 to 6 | V    |    |
| I <sub>O</sub>  | Output current  |                                    |  | ±15       | mA   |    |
| ESD             | Electrostatic discharge   | Human Body Model                   | JEDEC Standard 22, Test Method A114-C.01 | All pins  | ±4   | kV |
|                 |   | Field-Induced-Charged Device Model | JEDEC Standard 22, Test Method C101      |           | ±1   |    |
|                 |   | Machine Model                      | ANSI/ESDS5.2-1996                        |           | ±200 | V  |
| T <sub>J</sub>  | Maximum junction temperature  |                                    |  | 170       | °C   |    |

- (1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values are with respect to network ground terminal and are peak voltage values.

## RECOMMENDED OPERATING CONDITIONS

|                   |   |          | MIN  | TYP | MAX             | UNIT |
|-------------------|---|----------|------|-----|-----------------|------|
| V <sub>CC</sub>   | Supply voltage <sup>(1)</sup> , V <sub>CC1</sub> , V <sub>CC2</sub>                         |          | 3.15 |     | 5.5             | V    |
| I <sub>OH</sub>   | High-level output current   |          |      |     | 4               | mA   |
| I <sub>OL</sub>   | Low-level output current  |          | −4   |     |                 | mA   |
| t <sub>ui</sub>   | Input pulse width   | ISO724xA | 1    |     |                 | μs   |
| 1/t <sub>ui</sub> | Signaling rate  | ISO724xA | 0    |     | 1000            | kbps |
| V <sub>IH</sub>   | High-level input voltage (IN) (EN on all devices)   | ISO724xA | 2    |     | V <sub>CC</sub> | V    |
| V <sub>IL</sub>   | Low-level input voltage (IN) (EN on all devices)  |          | 0    |     | 0.8             | V    |
| T <sub>J</sub>    | Junction temperature  |          |      |     | 150             | °C   |
| H                 | External magnetic field-strength immunity per IEC 61000-4-8 and IEC 61000-4-9 certification |          |      |     | 1000            | A/m  |

- (1) For the 5-V operation, V<sub>CC1</sub> or V<sub>CC2</sub> is specified from 4.5 V to 5.5 V.  
For the 3-V operation, V<sub>CC1</sub> or V<sub>CC2</sub> is specified from 3.15 V to 3.6 V.

## IEC 60747-5-2 INSULATION CHARACTERISTICS<sup>(1)</sup>

over recommended operating conditions (unless otherwise noted)

| PARAMETER         |                                    | TEST CONDITIONS   | SPECIFICATIONS   | UNIT |
|-------------------|------------------------------------|---|------------------|------|
| V <sub>IORM</sub> | Maximum working insulation voltage |   | 560              | V    |
| V <sub>PR</sub>   | Input to output test voltage       | After Input/Output Safety Test Subgroup 2/3<br>V <sub>PR</sub> = V <sub>IORM</sub> × 1.2, t = 10 s,<br>Partial discharge < 5 pC | 672              | V    |
|                   |                                    | Method a, V <sub>PR</sub> = V <sub>IORM</sub> × 1.6,<br>Type and sample test with t = 10 s,<br>Partial discharge < 5 pC         | 896              | V    |
|                   |                                    | Method b1, V <sub>PR</sub> = V <sub>IORM</sub> × 1.875,<br>100 % Production test with t = 1 s,<br>Partial discharge < 5 pC      | 1050             | V    |
| V <sub>IOTM</sub> | Transient overvoltage              | t = 60 s  | 4000             | V    |
| R <sub>S</sub>    | Insulation resistance              | V <sub>IO</sub> = 500 V at T <sub>S</sub>   | >10 <sup>9</sup> | Ω    |
|                   | Pollution degree                   |   | 2                |      |

- (1) Climatic Classification 40/125/21

## ELECTRICAL CHARACTERISTICS: $V_{CC1}$ and $V_{CC2}$ at 5-V<sup>(1)</sup> OPERATION

, over recommended operating conditions (unless otherwise noted)

| PARAMETER                  |                                |           | TEST CONDITIONS  | MIN                   | TYP | MAX | UNIT  |
|----------------------------|--------------------------------|-----------|--|-----------------------|-----|-----|-------|
| SUPPLY CURRENT             |                                |           |  |                       |     |     |       |
| I <sub>CC1</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |                       | 1   | 3   | mA    |
|                            |                                | 1 Mbps    |  |                       | 1   | 3   |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 6.5 | 11  | mA    |
|                            |                                | 1 Mbps    |  |                       |     |     |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 10  | 16  | mA    |
|                            |                                | 1 Mbps    |  |                       | 10  | 16  |       |
| I <sub>CC2</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |                       | 15  | 22  | mA    |
|                            |                                | 1 Mbps    |  |                       | 16  | 22  |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 13  | 20  | mA    |
|                            |                                | 1 Mbps    |  |                       | 13  | 20  |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 10  | 16  | mA    |
|                            |                                | 1 Mbps    |  |                       | 10  | 16  |       |
| ELECTRICAL CHARACTERISTICS |                                |           |  |                       |     |     |       |
| I <sub>OFF</sub>           | Sleep mode output current      |           | EN at 0 V, Single channel  |                       | 0   |     | μA    |
| V <sub>OH</sub>            | High-level output voltage      |           | I <sub>OH</sub> = −4 mA, See <a href="#">Figure 1</a>  | V <sub>CC</sub> − 0.8 |     |     | V     |
|                            |                                |           | I <sub>OH</sub> = −20 μA, See <a href="#">Figure 1</a>   | V <sub>CC</sub> − 0.1 |     |     |       |
| V <sub>OL</sub>            | Low-level output voltage       |           | I <sub>OL</sub> = 4 mA, See <a href="#">Figure 1</a>   |                       |     | 0.4 | V     |
|                            |                                |           | I <sub>OL</sub> = 20 μA, See <a href="#">Figure 1</a>  |                       |     | 0.1 |       |
| V <sub>I(HYS)</sub>        | Input voltage hysteresis       |           |  | 150                   |     |     | mV    |
| I <sub>IH</sub>            | High-level input current       |           | IN from 0 V to V <sub>CC</sub>   |                       |     | 10  | μA    |
| I <sub>IL</sub>            | Low-level input current        |           |  | −10                   |     |     |       |
| C <sub>I</sub>             | Input capacitance to ground    |           | IN at V <sub>CC</sub> , V <sub>I</sub> = 0.4 sin (4E6πt)   | 2                     |     |     | pF    |
| CMTI                       | Common-mode transient immunity |           | V <sub>I</sub> = V <sub>CC</sub> or 0 V, See <a href="#">Figure 4</a>  | 25                    | 50  |     | kV/μs |

- (1) For the 5-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 4.5 V to 5.5 V.  
For the 3-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 3.15 V to 3.6 V.

## SWITCHING CHARACTERISTICS: $V_{CC1}$ and $V_{CC2}$ at 5-V OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER             |   | TEST CONDITIONS              | MIN | TYP | MAX | UNIT    |
|-----------------------|---|------------------------------|-----|-----|-----|---------|
| $t_{PLH}$ , $t_{PHL}$ | Propagation delay   | See <a href="#">Figure 1</a> | 40  |     | 95  | ns      |
| PWD                   | Pulse-width distortion <sup>(1)</sup> $ t_{PHL} - t_{PLH} $ |                              |     |     | 10  |         |
| $t_{sk(o)}$           | Channel-to-channel output skew <sup>(2)</sup>               |                              |     |     | 2   | ns      |
| $t_r$                 | Output signal rise time                                     | See <a href="#">Figure 1</a> |     | 2   |     | ns      |
| $t_f$                 | Output signal fall time                                     |                              |     | 2   |     |         |
| $t_{PHZ}$             | Propagation delay, high-level-to-high-impedance output      | See <a href="#">Figure 2</a> |     | 15  | 20  | ns      |
| $t_{PZH}$             | Propagation delay, high-impedance-to-high-level output      |                              |     | 15  | 20  |         |
| $t_{PLZ}$             | Propagation delay, low-level-to-high-impedance output       |                              |     | 15  | 20  |         |
| $t_{PZL}$             | Propagation delay, high-impedance-to-low-level output       |                              |     | 15  | 20  |         |
| $t_{fs}$              | Failsafe output delay time from input power loss            | See <a href="#">Figure 3</a> |     | 12  |     | $\mu$ s |

- (1) Also referred to as pulse skew.  
(2)  $t_{sk(o)}$  is the skew between specified outputs of a single device with all driving inputs connected together and the outputs switching in the same direction while driving identical specified loads.

## ELECTRICAL CHARACTERISTICS: $V_{CC1}$ at 5-V, $V_{CC2}$ at 3.3-V<sup>(1)</sup> OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER                  |                                |           | TEST CONDITIONS  |  | MIN                | TYP                   | MAX                   | UNIT  |
|----------------------------|--------------------------------|-----------|--|--|--------------------|-----------------------|-----------------------|-------|
| SUPPLY CURRENT             |                                |           |  |  |                    |                       |                       |       |
| I <sub>CC1</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |  | 1                  |                       | 3                     | mA    |
|                            |                                | 1 Mbps    |  |  | 1                  |                       | 3                     |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |  | 6.5                |                       | 11                    | mA    |
|                            |                                | 1 Mbps    |  |  |                    |                       |                       |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |  | 10                 |                       | 16                    | mA    |
|                            |                                | 1 Mbps    |  |  | 10                 |                       | 16                    |       |
| I <sub>CC2</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |  | 9.5                |                       | 15                    | mA    |
|                            |                                | 1 Mbps    |  |  | 10                 |                       | 15                    |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |  | 8                  |                       | 13                    | mA    |
|                            |                                | 1 Mbps    |  |  | 8                  |                       | 13                    |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |  | 6                  |                       | 10                    | mA    |
|                            |                                | 1 Mbps    |  |  | 6                  |                       | 10                    |       |
| ELECTRICAL CHARACTERISTICS |                                |           |  |  |                    |                       |                       |       |
| I <sub>OFF</sub>           | Sleep mode output current      |           | EN at 0 V, Single channel  |  | 0                  |                       | μA                    |       |
| V <sub>OH</sub>            | High-level output voltage      |           | I <sub>OH</sub> = −4 mA, See <a href="#">Figure 1</a>  |  | ISO7240A           | V <sub>CC</sub> − 0.4 |                       | V     |
|                            |                                |           |  |  | ISO724x (5-V side) | V <sub>CC</sub> − 0.8 |                       |       |
|                            |                                |           | I <sub>OH</sub> = −20 μA, See <a href="#">Figure 1</a>   |  |                    |                       | V <sub>CC</sub> − 0.1 |       |
| V <sub>OL</sub>            | Low-level output voltage       |           | I <sub>OL</sub> = 4 mA, See <a href="#">Figure 1</a>   |  |                    |                       | 0.4                   | V     |
|                            |                                |           | I <sub>OL</sub> = 20 μA, See <a href="#">Figure 1</a>  |  |                    |                       | 0.1                   |       |
| V <sub>I(HYS)</sub>        | Input voltage hysteresis       |           |  |  | 150                |                       | mV                    |       |
| I <sub>IH</sub>            | High-level input current       |           | IN from 0 V to V <sub>CC</sub>   |  |                    |                       | 10                    | μA    |
| I <sub>IL</sub>            | Low-level input current        |           |  |  | −10                |                       |                       |       |
| C <sub>I</sub>             | Input capacitance to ground    |           | IN at V <sub>CC</sub> , V <sub>I</sub> = 0.4 sin (4E6πt)   |  | 2                  |                       | pF                    |       |
| CMTI                       | Common-mode transient immunity |           | V <sub>I</sub> = V <sub>CC</sub> or 0 V, See <a href="#">Figure 4</a>  |  | 25                 |                       | 50                    | kV/μs |

- (1) For the 5-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 4.5 V to 5.5 V.  
For the 3-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 3.15 V to 3.6 V.

## SWITCHING CHARACTERISTICS: $V_{CC1}$ at 5-V, $V_{CC2}$ at 3.3-V OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER                           |  | TEST CONDITIONS              | MIN | TYP | MAX | UNIT |
|-------------------------------------|--|------------------------------|-----|-----|-----|------|
| t <sub>PLH</sub> , t <sub>PHL</sub> | Propagation delay  | See <a href="#">Figure 1</a> | 40  |     | 100 | ns   |
| PWD                                 | Pulse-width distortion <sup>(1)</sup>  t <sub>PHL</sub> – t <sub>PLH</sub> |                              |     |     | 11  |      |
| t <sub>sk(o)</sub>                  | Channel-to-channel output skew <sup>(2)</sup>                              |                              |     |     | 3   | ns   |
|                                     |  |                              |     | 0   | 1   |      |
| t <sub>r</sub>                      | Output signal rise time  | See <a href="#">Figure 1</a> |     | 2   |     | ns   |
| t <sub>f</sub>                      | Output signal fall time  |                              |     | 2   |     |      |
| t <sub>PHZ</sub>                    | Propagation delay, high-level-to-high-impedance output                     | See <a href="#">Figure 2</a> |     | 15  | 20  | ns   |
| t <sub>PZH</sub>                    | Propagation delay, high-impedance-to-high-level output                     |                              |     | 15  | 20  |      |
| t <sub>PLZ</sub>                    | Propagation delay, low-level-to-high-impedance output                      |                              |     | 15  | 20  |      |
| t <sub>PZL</sub>                    | Propagation delay, high-impedance-to-low-level output                      |                              |     | 15  | 20  |      |
| t <sub>fs</sub>                     | Failsafe output delay time from input power loss                           | See <a href="#">Figure 3</a> |     | 18  |     | μs   |

- (1) Also known as pulse skew  
(2)  $t_{sk(o)}$  is the skew between specified outputs of a single device with all driving inputs connected together and the outputs switching in the same direction while driving identical specified loads.

## ELECTRICAL CHARACTERISTICS: $V_{CC1}$ at 3.3-V, $V_{CC2}$ at 5-V<sup>(1)</sup> OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER                  |                                |           | TEST CONDITIONS  |                       | MIN                   | TYP | MAX | UNIT  |
|----------------------------|--------------------------------|-----------|--|-----------------------|-----------------------|-----|-----|-------|
| SUPPLY CURRENT             |                                |           |  |                       |                       |     |     |       |
| I <sub>CC1</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |                       | 0.5                   |     | 1   | mA    |
|                            |                                | 1 Mbps    |  |                       | 1                     |     | 2   |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 4                     |     | 7   | mA    |
|                            |                                | 1 Mbps    |  |                       | 4                     |     | 7   |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 6                     |     | 10  | mA    |
|                            |                                | 1 Mbps    |  |                       | 6                     |     | 10  |       |
| I <sub>CC2</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>2</sub> at 3 V                         |                       | 15                    |     | 22  | mA    |
|                            |                                | 1 Mbps    |  |                       | 16                    |     | 22  |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 13                    |     | 20  | mA    |
|                            |                                | 1 Mbps    |  |                       | 13                    |     | 20  |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, All channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 10                    |     | 16  | mA    |
|                            |                                | 1 Mbps    |  |                       | 10                    |     | 16  |       |
| ELECTRICAL CHARACTERISTICS |                                |           |  |                       |                       |     |     |       |
| I <sub>OFF</sub>           | Sleep mode output current      |           | EN at V <sub>CC</sub> , Single channel   |                       | 0                     |     | μA  |       |
| V <sub>OH</sub>            | High-level output voltage      |           | I <sub>OH</sub> = −4 mA, See <a href="#">Figure 1</a>  | ISO7240A              | V <sub>CC</sub> − 0.4 |     | V   |       |
|                            |                                |           |  | ISO724x (5-V side)    | V <sub>CC</sub> − 0.8 |     |     |       |
|                            |                                |           | I <sub>OH</sub> = −20 μA, See <a href="#">Figure 1</a>   | V <sub>CC</sub> − 0.1 |                       |     |     |       |
| V <sub>OL</sub>            | Low-level output voltage       |           | I <sub>OL</sub> = 4 mA, See <a href="#">Figure 1</a>   |                       |                       | 0.4 |     | V     |
|                            |                                |           | I <sub>OL</sub> = 20 μA, See <a href="#">Figure 1</a>  |                       |                       | 0.1 |     |       |
| V <sub>I(HYS)</sub>        | Input voltage hysteresis       |           |  |                       | 150                   |     | mV  |       |
| I <sub>IH</sub>            | High-level input current       |           | IN from 0 V to V <sub>CC</sub>   |                       | 10                    |     | μA  |       |
| I <sub>IL</sub>            | Low-level input current        |           |  |                       | −10                   |     |     |       |
| C <sub>I</sub>             | Input capacitance to ground    |           | IN at V <sub>CC</sub> , V <sub>I</sub> = 0.4 sin (4E6πt)   |                       | 2                     |     | pF  |       |
| CMTI                       | Common-mode transient immunity |           | V <sub>I</sub> = V <sub>CC</sub> or 0 V, See <a href="#">Figure 4</a>  |                       | 25                    |     | 50  | kV/μs |

- (1) For the 5-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 4.5 V to 5.5 V.  
For the 3-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 3.15 V to 3.6 V.

## SWITCHING CHARACTERISTICS: $V_{CC1}$ at 3.3-V and $V_{CC2}$ at 5-V OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER             |   | TEST CONDITIONS              | MIN | TYP | MAX | UNIT    |
|-----------------------|---|------------------------------|-----|-----|-----|---------|
| $t_{PLH}$ , $t_{PHL}$ | Propagation delay   | See <a href="#">Figure 1</a> | 40  | 100 |     | ns      |
| PWD                   | Pulse-width distortion <sup>(1)</sup> $ t_{PHL} - t_{PLH} $ |                              |     | 11  |     |         |
| $t_{sk(o)}$           | Channel-to-channel output skew <sup>(2)</sup>               |                              |     | 2.5 |     | ns      |
|                       |   |                              |     | 0   | 1   |         |
| $t_r$                 | Output signal rise time                                     | See <a href="#">Figure 1</a> |     | 2   |     | ns      |
| $t_f$                 | Output signal fall time                                     |                              |     | 2   |     |         |
| $t_{PHZ}$             | Propagation delay, high-level-to-high-impedance output      | See <a href="#">Figure 2</a> |     | 15  | 20  | ns      |
| $t_{PZH}$             | Propagation delay, high-impedance-to-high-level output      |                              |     | 15  | 20  |         |
| $t_{PLZ}$             | Propagation delay, low-level-to-high-impedance output       |                              |     | 15  | 20  |         |
| $t_{PZL}$             | Propagation delay, high-impedance-to-low-level output       |                              |     | 15  | 20  |         |
| $t_{fs}$              | Failsafe output delay time from input power loss            | See <a href="#">Figure 3</a> |     | 12  |     | $\mu s$ |

- (1) Also known as pulse skew  
(2)  $t_{sk(o)}$  is the skew between specified outputs of a single device with all driving inputs connected together and the outputs switching in the same direction while driving identical specified loads.

## ELECTRICAL CHARACTERISTICS: $V_{CC1}$ and $V_{CC2}$ at 3.3 V<sup>(1)</sup> OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER                  |                                |           | TEST CONDITIONS  | MIN                   | TYP | MAX | UNIT  |
|----------------------------|--------------------------------|-----------|--|-----------------------|-----|-----|-------|
| SUPPLY CURRENT             |                                |           |  |                       |     |     |       |
| I <sub>CC1</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>2</sub> at 3 V                         |                       | 0.5 | 1   | mA    |
|                            |                                | 1 Mbps    |  |                       | 1   | 2   |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 4   | 7   | mA    |
|                            |                                | 1 Mbps    |  |                       | 4   | 7   |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 6   | 10  |       |
|                            |                                | 1 Mbps    |  |                       | 6   | 10  |       |
| I <sub>CC2</sub>           | ISO7240A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>2</sub> at 3 V                         |                       | 9.5 | 15  | mA    |
|                            |                                | 1 Mbps    |  |                       | 10  | 15  |       |
|                            | ISO7241A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 8   | 13  | mA    |
|                            |                                | 1 Mbps    |  |                       | 8   | 13  |       |
|                            | ISO7242A                       | Quiescent | V <sub>I</sub> = V <sub>CC</sub> or 0 V, all channels, no load, EN <sub>1</sub> at 3 V, EN <sub>2</sub> at 3 V |                       | 6   | 10  |       |
|                            |                                | 1 Mbps    |  |                       | 6   | 10  |       |
| ELECTRICAL CHARACTERISTICS |                                |           |  |                       |     |     |       |
| I <sub>OFF</sub>           | Sleep mode output current      |           | EN at 0 V, single channel  |                       | 0   |     | μA    |
| V <sub>OH</sub>            | High-level output voltage      |           | I <sub>OH</sub> = −4 mA, See <a href="#">Figure 1</a>  | V <sub>CC</sub> − 0.4 |     |     | V     |
|                            |                                |           | I <sub>OH</sub> = −20 μA, See <a href="#">Figure 1</a>   | V <sub>CC</sub> − 0.1 |     |     |       |
| V <sub>OL</sub>            | Low-level output voltage       |           | I <sub>OL</sub> = 4 mA, See <a href="#">Figure 1</a>   |                       |     | 0.4 | V     |
|                            |                                |           | I <sub>OL</sub> = 20 μA, See <a href="#">Figure 1</a>  |                       |     | 0.1 |       |
| V <sub>I(HYS)</sub>        | Input voltage hysteresis       |           |  | 150                   |     |     | mV    |
| I <sub>IH</sub>            | High-level input current       |           | IN from 0 V or V <sub>CC</sub>   |                       |     | 10  | μA    |
| I <sub>IL</sub>            | Low-level input current        |           |  | −10                   |     |     |       |
| C <sub>I</sub>             | Input capacitance to ground    |           | IN at V <sub>CC</sub> , V <sub>I</sub> = 0.4 sin (4E6πt)   | 2                     |     |     | pF    |
| CMTI                       | Common-mode transient immunity |           | V <sub>I</sub> = V <sub>CC</sub> or 0 V, See <a href="#">Figure 4</a>  | 25                    | 50  |     | kV/μs |

- (1) For the 5-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 4.5 V to 5.5 V.  
For the 3-V operation,  $V_{CC1}$  or  $V_{CC2}$  is specified from 3.15 V to 3.6 V.


## SWITCHING CHARACTERISTICS: $V_{CC1}$ and $V_{CC2}$ at 3.3-V OPERATION

over recommended operating conditions (unless otherwise noted)

| PARAMETER             |  | TEST CONDITIONS              | MIN | TYP | MAX | UNIT    |
|-----------------------|--|------------------------------|-----|-----|-----|---------|
| $t_{PLH}$ , $t_{PHL}$ | Propagation delay                                      | See <a href="#">Figure 1</a> | 45  |     | 110 | ns      |
| PWD                   | Pulse-width distortion $ t_{PHL} - t_{PLH} ^{(1)}$     |                              |     |     | 12  |         |
| $t_{sk(o)}$           | Channel-to-channel output skew <sup>(2)</sup>          |                              |     | 3.5 |     | ns      |
| $t_r$                 | Output signal rise time                                | See <a href="#">Figure 1</a> |     | 0   | 1   |         |
| $t_f$                 | Output signal fall time                                |                              |     | 2   |     |         |
| $t_{PHZ}$             | Propagation delay, high-level-to-high-impedance output | See <a href="#">Figure 2</a> |     | 15  | 20  | ns      |
| $t_{PZH}$             | Propagation delay, high-impedance-to-high-level output |                              |     | 15  | 20  |         |
| $t_{PLZ}$             | Propagation delay, low-level-to-high-impedance output  |                              |     | 15  | 20  |         |
| $t_{PZL}$             | Propagation delay, high-impedance-to-low-level output  |                              |     | 15  | 20  |         |
| $t_{fs}$              | Failsafe output delay time from input power loss       | See <a href="#">Figure 3</a> |     | 18  |     | $\mu s$ |


- (1) Also referred to as pulse skew.  
(2)  $t_{sk(o)}$  is the skew between specified outputs of a single device with all driving inputs connected together and the outputs switching in the same direction while driving identical specified loads.

## PARAMETER MEASUREMENT INFORMATION



- The input pulse is supplied by a generator having the following characteristics:  $PRR \leq 50$  kHz, 50% duty cycle,  $t_r \leq 3$  ns,  $t_f \leq 3$  ns,  $Z_O = 50 \Omega$ .
- $C_L = 15$  pF and includes instrumentation and fixture capacitance within  $\pm 20\%$ .

**Figure 1. Switching Characteristic Test Circuit and Voltage Waveforms**




- The input pulse is supplied by a generator having the following characteristics:  $PRR \leq 50$  kHz, 50% duty cycle,  $t_r \leq 3$  ns,  $t_f \leq 3$  ns,  $Z_O = 50 \Omega$ .
- $C_L = 15$  pF and includes instrumentation and fixture capacitance within  $\pm 20\%$ .

**Figure 2. Enable/Disable Propagation Delay Time Test Circuit and Waveform**




## PARAMETER MEASUREMENT INFORMATION (continued)



- $C_L = 15 \text{ pF}$  and includes instrumentation and fixture capacitance within  $\pm 20\%$ .
- The input pulse is supplied by a generator having the following characteristics:  $\text{PRR} \leq 50 \text{ kHz}$ , 50% duty cycle,  $t_r \leq 3 \text{ ns}$ ,  $t_f \leq 3 \text{ ns}$ ,  $Z_0 = 50 \Omega$ .

**Figure 3. Failsafe Delay Time Test Circuit and Voltage Waveforms**



- $C_L = 15 \text{ pF}$  and includes instrumentation and fixture capacitance within  $\pm 20\%$ .
- The input pulse is supplied by a generator having the following characteristics:  $\text{PRR} \leq 50 \text{ kHz}$ , 50% duty cycle,  $t_r \leq 3 \text{ ns}$ ,  $t_f \leq 3 \text{ ns}$ ,  $Z_0 = 50 \Omega$ .

**Figure 4. Common-Mode Transient Immunity Test Circuit and Voltage Waveform**

## DEVICE INFORMATION

### PACKAGE CHARACTERISTICS

| PARAMETER  | TEST CONDITIONS   | MIN               | TYP | MAX | UNIT |
|--|---|-------------------|-----|-----|------|
| L(I01) Minimum air gap (Clearance)                               | Shortest terminal-to-terminal distance through air  | 8.34              |     |     | mm   |
| L(I02) Minimum external tracking (Creepage)                      | Shortest terminal-to-terminal distance across the package surface   | 8.1               |     |     | mm   |
| C <sub>TI</sub> Tracking resistance (comparative tracking index) | DIN IEC 60112/VDE 0303 Part 1   | ≥ 175             |     |     | V    |
| Minimum Internal Gap (Internal Clearance)                        | Distance through the insulation   | 0.008             |     |     | mm   |
| R <sub>IO</sub> Isolation resistance                             | Input to output, V <sub>IO</sub> = 500 V, all pins on each side of the barrier tied together creating a two-terminal device | >10 <sup>12</sup> |     |     | Ω    |
| C <sub>IO</sub> Barrier capacitance Input to output              | V <sub>I</sub> = 0.4 sin (4E6πt)  |                   | 2   |     | pF   |
| C <sub>I</sub> Input capacitance to ground                       | V <sub>I</sub> = 0.4 sin (4E6πt)  |                   | 2   |     | pF   |

### IEC 60664-1 RATINGS TABLE


| PARAMETER                   | TEST CONDITIONS               | SPECIFICATION |
|-----------------------------|-------------------------------|---------------|
| Basic isolation group       | Material group                | IIIa          |
| Installation classification | Rated mains voltage ≤150 VRMS | I-IV          |
|                             | Rated mains voltage ≤300 VRMS | I-III         |

### REGULATORY INFORMATION

| VDE                                  | CSA  | UL   |
|--------------------------------------|--|--|
| Certified according to IEC 60747-5-2 | Approved under CSA Component Acceptance Notice | Recognized under 1577 Component Recognition Program <sup>(1)</sup> |
| File Number: 40016131                | File Number: 1698195                           | File Number: E181974   |

(1) Production tested ≥ 3000 Vrms for 1 second in accordance with UL 1577.

### DEVICE I/O SCHEMATICS



## THERMAL CHARACTERISTICS

over recommended operating conditions (unless otherwise noted)

| PARAMETER  | TEST CONDITIONS   | MIN | TYP  | MAX | UNIT |
|--|---|-----|------|-----|------|
| $\theta_{JA}$ Junction-to-air                      | Low-K Thermal Resistance <sup>(1)</sup>   |     | 168  |     | °C/W |
|  | High-K Thermal Resistance   |     | 96.1 |     |      |
| $\theta_{JB}$ Junction-to-Board Thermal Resistance |   |     | 61   |     | °C/W |
| $\theta_{JC}$ Junction-to-Case Thermal Resistance  |   |     | 48   |     | °C/W |
| $P_D$ Device Power Dissipation                     | $V_{CC1} = V_{CC2} = 5.5\text{ V}$ , $T_J = 150^\circ\text{C}$ , $C_L = 15\text{ pF}$ ,<br>Input a 50% duty cycle square wave |     |      | 220 | mW   |

(1) Tested in accordance with the Low-K or High-K thermal metric definitions of EIA/JESD51-3 for leaded surface mount packages.

## TYPICAL CHARACTERISTIC CURVES




Figure 5.




Figure 6.




Figure 7.




Figure 8.

## APPLICATION INFORMATION




Figure 9. Typical ISO7240A Application Circuit

## LIFE EXPECTANCY vs. WORKING VOLTAGE




Figure 10. Time-Dependant Dielectric Breakdown Testing Results

## PRODUCT NOTIFICATION

An ISO724xA anomaly occurs when a negative-going pulse below the specified 1  $\mu$ s minimum bit width is input to the device. The output locks in a logic-low condition until the next rising edge occurs after a 1  $\mu$ s period.

Positive noise edges in pulses of less than the minimum specified 1  $\mu$ s have no effect on the device, and are properly filtered.

To prevent noise from interfering with ISO724xA performance, it is recommended that an appropriately sized capacitor be placed on each input of the device




Figure 11. ISO724xA Anomaly

## REVISION HISTORY

| Changes from Original (May 2008) to Revision A   | Page    |
|--|---------|
| <ul style="list-style-type: none"> <li>Changed In the PACKAGE CHARACTERISTICS table, line 1, change L<sub>(IO1)</sub> MIN value from 7.7mm to 8.34mm. ....</li> </ul>  | 10      |
| Changes from Revision A (July 2008) to Revision B  | Page    |
| <ul style="list-style-type: none"> <li>Added information to the 1st Feature bullet to include CSA and IEC 60950-1 certification .....</li> <li>Changed <a href="#">Figure 9</a> From: 20mm max.from V<sub>CCx</sub> To: 2mm max. from V<sub>CCx</sub>. ....</li> </ul> | 1<br>12 |
| Changes from Revision B (December 2008) to Revision C  | Page    |
| <ul style="list-style-type: none"> <li>Changed I<sub>CC1</sub> for Quiescent and 1Mbps From: 10mA To: 11mA .....</li> <li>Changed I<sub>CC1</sub> for Quiescent and 1Mbps From: 10mA To: 11mA .....</li> </ul>   | 4<br>5  |
| Changes from Revision C (March 2009) to Revision D   | Page    |
| <ul style="list-style-type: none"> <li>Changed The Input circuit in the DEVICE I/O SCHEMATICS illustration. ....</li> </ul>  | 10      |

| Changes from Revision D (December 2009) to Revision E  | Page |
|--|------|
| • Added the IEC 60747-5-2 INSULATION CHARACTERISTIC table .....  | 3    |
| • Added C <sub>TI</sub> - Tracking resistance (comparative tracking index to the PACKAGE CHARACTERISTICS table ..... | 10   |
| • Added the IEC 60664-1 RATINGS TABLE .....  | 10   |

**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| ISO7240ADW       | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7240ADWG4     | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7240ADWR      | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7240ADWRG4    | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7241ADW       | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7241ADWG4     | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7241ADWR      | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7241ADWRG4    | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7242ADW       | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7242ADWG4     | ACTIVE                | SOIC         | DW              | 16   | 40          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7242ADWR      | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |
| ISO7242ADWRG4    | ACTIVE                | SOIC         | DW              | 16   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-3-260C-168 HR          |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF ISO7241A :**

- Enhanced Product: [ISO7241A-EP](#)

NOTE: Qualified Version Definitions:

- Enhanced Product - Supports Defense, Aerospace and Medical Applications



**TAPE AND REEL INFORMATION**


\*All dimensions are nominal


| Device      | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| ISO7240ADWR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |
| ISO7241ADWR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |
| ISO7242ADWR | SOIC         | DW              | 16   | 2000 | 330.0              | 16.4               | 10.75   | 10.7    | 2.7     | 12.0    | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal


| Device      | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| ISO7240ADWR | SOIC         | DW              | 16   | 2000 | 358.0       | 335.0      | 35.0        |
| ISO7241ADWR | SOIC         | DW              | 16   | 2000 | 358.0       | 335.0      | 35.0        |
| ISO7242ADWR | SOIC         | DW              | 16   | 2000 | 358.0       | 335.0      | 35.0        |



NOTES: A. All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M-1994.  
B. This drawing is subject to change without notice.  
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).  
D. Falls within JEDEC MS-013 variation AA.

DW (R-PDSO-G16)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Refer to IPC7351 for alternate board design.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

|                             |  |
|-----------------------------|--|
| Audio                       | <a href="http://www.ti.com/audio">www.ti.com/audio</a>             |
| Amplifiers                  | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             |
| Data Converters             | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     |
| DLP® Products               | <a href="http://www.dlp.com">www.dlp.com</a>                       |
| DSP                         | <a href="http://dsp.ti.com">dsp.ti.com</a>                         |
| Clocks and Timers           | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>           |
| Interface                   | <a href="http://interface.ti.com">interface.ti.com</a>             |
| Logic                       | <a href="http://logic.ti.com">logic.ti.com</a>                     |
| Power Mgmt                  | <a href="http://power.ti.com">power.ti.com</a>                     |
| Microcontrollers            | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> |
| RFID                        | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>               |
| RF/IF and ZigBee® Solutions | <a href="http://www.ti.com/lprf">www.ti.com/lprf</a>               |

### Applications

|                               |  |
|-------------------------------|--|
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Transportation and Automotive | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |
| Wireless                      | <a href="http://www.ti.com/wireless-apps">www.ti.com/wireless-apps</a>                   |

TI E2E Community Home Page

[e2e.ti.com](http://e2e.ti.com)

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2011, Texas Instruments Incorporated